

PERISTALTIC PUMP MP3-B1 TIMER

Data
Sheet

DESCRIPTION

- ✓ Peristaltic pump with ON/OFF timer regulation, on a 0 ÷ 25 interval, trimmer regulation
- ✓ Backplate for wall mounting
- ✓ Automatic Bleed
- ✓ PP body reinforced with 30% talc
- ✓ Polycarbonate front panel
- ✓ Standard Power Supply 230 Vac
- ✓ 100 % Made in Italy
- ✓ CE regulation compliant
- ✓ Small size
- ✓ Easy to install
- ✓ Requires minimal maintenance
- ✓ Safe and reliable
- ✓ Panel mounting
- ✓ PBT roller holder
- ✓ Delrin roller (self-lubricating)



DESCRIPTION		
	Standard material	Upon request
Standard version		
Pump body	PP reinforced with 30 % fiber glass	-----
Roller	DELRIN	-----
Tube	Santoprene	Silicon / Tygon
Consumption	35 Watts	-----
Net Weight	0,35 kg.	-----
Nuts	PP 1/8"	-----
Fittings	PP 4 x 6 mm	Rubber holder Hostaform
Power roller	230 Vac	24 VCC

PERISTALTIC PUMP MP3-B1 TIMER

Data
Sheet

SPECIFICATIONS											
Standard	Max lt/h	pressure		Max cc / min	Tube	Measure	Pump body	Watt	RPM	Weight	
		Bar	PSI							kg.	Lbs
230VAC VERSION											
1,5 - 01	1,5	01	14,7	25	Santoprene	5,8 x 9,4	PP	35	10	0,35	0,8
03 - 01	03	01	14,7	50	Santoprene	5,8 x 9,4	PP	35	20	0,35	0,8
04 - 01	04	01	14,7	66,67	Santoprene	5,8 x 9,4	PP	35	40	0,35	0,8
0,5 - 03	0,5	03	44,1	8,34	Silicon	5 x 10	PP	35	10	0,35	0,8
01 - 03	01	03	44,1	16,67	Silicon	5 x 10	PP	35	20	0,35	0,8

